

MINO 60 direct / indirect high lumen ceiling /

suspended system

046-5023638H



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL9005 ¹

4360 lm/m

IP20

indirect 1440 lm

direct 2360 lm

total 3800 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

High Performance Opal

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

26.2 W

PC1 220-240V

145 lm/W

1 DALI Addr.

30 W/m

Physical

trim

length 872 mm


width 60 mm

height 80 mm

1.65 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



[046-5023638H] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

08.05.2024

Installation instructions



Lighting calculator

