

# FRAME 40 mid lumen

trim system

042-0116037 042-7006018 006-4230010Z



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Recessed	
black , RAL9005 <sup>1</sup>	
1200 lm/m	
IP20	
3600 lm	

## LED

3000 K	
CRI ≥ 90	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89	
MR 0.61	
MDER 0.55	

## Optical

Microprismatic	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	

## Electrical

DALI-2	
35 W	
PC1 220-240V	
103 lm/W	
12 W/m	

## Physical

trim	
length 3000 mm	
width 55 mm	
height 60 mm	
5.5 kg	

## Cutout


length 3010 mm	
width 45 mm	
min. ceiling thickness 8 mm	
max. ceiling thickness 25 mm	
recessed depth 100 mm	

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Lighting calculator



## Light distribution



## Product drawing

