

# MINO 60 CURVE 90° high lumen

ceiling / suspended system  
034-0951517H



|                |  |
|----------------|--|
| Project / Type |  |
| Notes          |  |
| Count / Date   |  |



### General

|                               |
|-------------------------------|
| Ceiling , Suspended           |
| white , RAL 9010 <sup>1</sup> |
| IP20                          |
| 2630 lm                       |
| 2230 lm/m                     |

### LED

|                          |
|--------------------------|
| 3000 K                   |
| CRI ≥ 80                 |
| L90 / 50000 h            |
| initial MacAdam ≤ 3 SDCM |
| MR 0.56                  |
| MDER 0.51                |

### Optical

|                          |
|--------------------------|
| High Performance Opal    |
| opal (lambertsch)        |
| PstLM ≤ 1.0 <sup>2</sup> |
| SVM ≤ 0.4 <sup>2</sup>   |

### Electrical


|                              |
|------------------------------|
| non DIM                      |
| 220-240 V                    |
| system 22.1 W                |
| system 119 lm/W <sup>3</sup> |
| PC1                          |
| 19 W/m                       |

### Physical

|                          |
|--------------------------|
| width 60 mm              |
| height 80 mm             |
| curve length 1178 mm     |
| centerline radius 750 mm |
| segment 90°              |
| 3 kg                     |

Circular segment of rolled aluminium profile, angular design, seamlessly welded; CURVE segment design 90°; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface white powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Installation instructions



### Lighting calculator



# MINO 60 CURVE 90° high lumen

ceiling / suspended system

034-0951517H



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000  | 40 000 | 50 000 |
|--------------------|------------------------------|--------|---|--------|--------|
| LLMF               | 0.98                         | 0.96   | 0.94  | 0.92   | 0.9    |
| LSF                | 1                            | 1      | 1   | 1      | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> Room Surface Maintenance Factor |        |        |
| MF                 | Maintenance Factor           |        | LLMF Lamp Lumens Maintenance Factor               |        |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF Lamp Survival Factor                          |        |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 9                  |
| B13                            | 13                 |
| B16                            | 15                 |
| B20                            | 18                 |
| C10                            | 18                 |
| C13                            | 26                 |
| C16                            | 30                 |
| C20                            | 36                 |

## Mounting accessories

### END CAPS

| TYPE   | COLOUR          | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|-----------------|------------|-------------------|
| 1 pair | traffic white   | 60-80-8    | 034-0902017       |
| 1 pair | jet black       | 60-80-8    | 034-0902018       |
| 1 pair | white aluminium | 60-80-8    | 034-090201G       |
| 1 pair | special colours | 60-80-8    | 034-090201X       |



## Mounting accessories

### CEILING CLIP

| COLOUR      | ARTICLE NUMBER(S) |
|-------------|-------------------|
| transparent | 034-11636         |



## Mounting accessories

### CABLE SUSPENSION

| ARTICLE NUMBER(S) |
|-------------------|
| 005-2122110       |



### CABLE RAIL

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 1200   | 005-2491110       |



## Electrical accessories

### THROUGH WIRE

| TYPE                                | ARTICLE NUMBER(S) |
|-------------------------------------|-------------------|
| 3 x 1,5 mm <sup>2</sup>   10 pieces | 004-90003         |
| 5 x 1,5 mm <sup>2</sup>   10 pieces | 004-90005         |



[034-0951517H] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

03.05.2025

# MINO 60 CURVE 90° high lumen

ceiling / suspended system  
034-0951517H



Project / Type

Notes

Count / Date

## Electrical accessories

### CANOPY / FEEDER CABLE

| TYPE                    | COLOUR        | L-W-H (MM) | ARTICLE NUMBER(S) |
|-------------------------|---------------|------------|-------------------|
| 3 x 1,5 mm <sup>2</sup> | traffic white | 90-90-22   | 005-2212317       |
| 3 x 1,5 mm <sup>2</sup> | jet black     | 90-90-22   | 005-2212318       |
| 5 x 1,5 mm <sup>2</sup> | pure white    | 90-90-22   | 005-2212417       |
| 5 x 1,5 mm <sup>2</sup> | jet black     | 90-90-22   | 005-2212418       |

