

MINO 60 CURVE high lumen


ceiling / suspended system
034-095063XZ



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours

2280 lm/m

IP20

1340 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

Microprismatic

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

13.0 W

PC1 220-240V

103 lm/W

1 DALI Addr.

22 W/m

Physical

width 60 mm

height 80 mm

curve length 589 mm


centerline radius 750 mm

segment 45°

1.8 kg

¹ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[‘034-095063XZ’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com