

MINO 60 CURVE mid lumen

ceiling / suspended system

034-094051GH



Project / Type

Notes

Count / Date



General

Ceiling , Suspended
grey , RAL9006 ¹
1590 lm/m
IP20
940 lm

LED

3000 K
CRI \geq 80
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam \leq 3 SDCM
MR 0.56
MDER 0.51

Optical

High Performance Opal
PstLM \leq 1.0 ²
SVM \leq 0.4 ²

Electrical


non DIM
8.7 W
PC1 220-240V
108 lm/W
15 W/m

Physical

width 60 mm
height 80 mm
curve length 589 mm
centerline radius 750 mm
segment 45°
1.65 kg

Circular segment of rolled aluminium profile, angular design, seamlessly welded; CURVE segment design 45°; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface grey powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

