

# MINO 60 high lumen

ceiling / suspended system

007-93M8037 006-16232G 046-4008017



Project / Type

Notes

Count / Date



### General

Ceiling , Suspended

white , RAL9010 <sup>1</sup>

1770 lm/m

IP20

4150 lm

### LED

3000 K

CRI ≥ 90

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

### Optical

Microprismatic

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

47 W

PC1 220-240V

88 lm/W

1 DALI Addr.

20 W/m

### Physical

trim

length 2344 mm


width 60 mm

height 80 mm

5.8 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator





# MINO 60 high lumen

ceiling / suspended system

007-93M8037 006-16232G 046-4008017



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000            | 40 000                          | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF               | 0.98                         | 0.96   | 0.94              | 0.92                            | 0.9    |
| LSF                | 1                            | 1      | 1                 | 1                               | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> | Room Surface Maintenance Factor |        |
| MF                 | Maintenance Factor           |        | LLMF              | Lamp Lumens Maintenance Factor  |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF               | Lamp Survival Faktor            |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 7                  |
| B13                            | 10                 |
| B16                            | 12                 |
| B20                            | 14                 |
| C10                            | 10                 |
| C13                            | 20                 |
| C16                            | 24                 |
| C20                            | 28                 |

## Mounting accessories

### END CAPS

| TYPE   | COLOUR          | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|-----------------|------------|-------------------|
| 1 pair | traffic white   | 60-40-4    | 046-5010017       |
| 1 pair | jet black       | 60-40-4    | 046-5010018       |
| 1 pair | white aluminium | 60-40-4    | 046-501001G       |
| 1 pair | special colours | 60-40-4    | 046-501001X       |



## Mounting accessories

### LINEAR CONNECTOR

| TYPE      | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece   | 005-40046         |
| 10 pieces | 005-40046.10      |



### OPAL COVER LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 006-14000         |

## Mounting accessories

### CEILING CLIP

| COLOUR      | ARTICLE NUMBER(S) |
|-------------|-------------------|
| transparent | 034-11636         |



## Mounting accessories

### CABLE SUSPENSION

| ARTICLE NUMBER(S) |
|-------------------|
| 005-2122110       |



### CABLE RAIL

| Ø (MM) | ARTICLE NUMBER(S) |
|--------|-------------------|
| 1200   | 005-2491110       |



[007-93M8037 006-16232G 046-4008017] The technical data represent rated values for an ambient temperature of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

or the luminous 28.05.2024



# MINO 60 high lumen

ceiling / suspended system

007-93M8037 006-16232G 046-4008017



Project / Type

Notes

Count / Date

## Electrical accessories

### THROUGH WIRE

| TYPE                                | ARTICLE NUMBER(S) |
|-------------------------------------|-------------------|
| 3 x 1,5 mm <sup>2</sup>   10 pieces | 004-90003         |
| 5 x 1,5 mm <sup>2</sup>   10 pieces | 004-90005         |



## Electrical accessories

### CANOPY / FEEDER CABLE

| TYPE                    | COLOUR        | ARTICLE NUMBER(S) |
|-------------------------|---------------|-------------------|
| 3 x 1,5 mm <sup>2</sup> | traffic white | 005-2212317       |
| 3 x 1,5 mm <sup>2</sup> | jet black     | 005-2212318       |
| 5 x 1,5 mm <sup>2</sup> | pure white    | 005-2212417       |
| 5 x 1,5 mm <sup>2</sup> | jet black     | 005-2212418       |

