

# MINO 60 high lumen

ceiling / suspended system

007-93M8537 006-16232H 046-4008017



Project / Type	
Notes	
Count / Date	



Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface white powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Product drawing



### General

Ceiling , Suspended	
white , RAL9010 <sup>1</sup>	
2360 lm/m	
IP20	
5530 lm	

### LED

3000 K	
CRI $\geq 80$	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam $\leq 3$ SDCM	
MR 0.56	
MDER 0.51	

### Optical

High Performance Opal	
PstLM $\leq 1.0$ <sup>2</sup>	
SVM $\leq 0.4$ <sup>2</sup>	

### Electrical

DALI-2	
47 W	
PC1 220-240V	
118 lm/W	
1 DALI Addr.	
20 W/m	

### Physical

trim	
length 2344 mm	
width 60 mm	
height 80 mm	
5.5 kg	

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

