

MINO 60 high lumen

ceiling / suspended system

007-93M8137 006-16232H 046-400801X



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface special colours powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Product drawing



General

| | |
|---------------------|--|
| Ceiling , Suspended | |
| special colours | |
| 2200 lm/m | |
| IP20 | |
| 5150 lm | |

LED

| | |
|--|--|
| 4000 K | |
| CRI ≥ 90 | |
| L90 / 50000 h | |
| photobio. safety RG 0 - no Risk | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 99 , R _f : 92 , R ₍₁₋₁₅₎ : 90 | |
| MR 0.81 | |
| MDER 0.74 | |

Optical

| | |
|-------------------------------|--|
| High Performance Opal | |
| PstLM ≤ 1.0 ¹ | |
| SVM ≤ 0.4 ¹ | |

Electrical

| | |
|--------------|--|
| DALI-2 | |
| 47 W | |
| PC1 220-240V | |
| 110 lm/W | |
| 1 DALI Addr. | |
| 20 W/m | |

Physical

| | |
|----------------|--|
| trim | |
| length 2344 mm | |
| width 60 mm | |
| height 80 mm | |
| 5.5 kg | |

¹ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

