

# MINO 60 high lumen

ceiling / suspended system

007-93M3037 006-16092Z 046-400301X



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Suspended	
special colours	
1780 lm/m	
IP20	
1550 lm	

## LED

3000 K	
CRI $\geq$ 90	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam $\leq$ 3 SDCM	
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89	
MR 0.61	
MDER 0.55	

## Optical

Microprismatic	
PstLM $\leq$ 1.0 <sup>1</sup>	
SVM $\leq$ 0.4 <sup>1</sup>	

## Electrical

DALI-2	
17.5 W	
PC1 220-240V	
89 lm/W	
1 DALI Addr.	
20 W/m	

## Physical

trim	
length 872 mm	
width 60 mm	
height 80 mm	
2.49 kg	

<sup>1</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator



# MINO 60 high lumen

ceiling / suspended system

007-93M3037 006-16092Z 046-400301X



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	18
B13	23
B16	28
B20	35
C10	30
C13	38
C16	46
C20	58

## Mounting accessories

### END CAPS

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
1 pair	traffic white	60-40-4	046-5010017
1 pair	jet black	60-40-4	046-5010018
1 pair	white aluminium	60-40-4	046-501001G
1 pair	special colours	60-40-4	046-501001X



## Mounting accessories

### LINEAR CONNECTOR

TYPE	ARTICLE NUMBER(S)
1 piece	005-40046
10 pieces	005-40046.10



### OPAL COVER LINEAR CONNECTOR

ARTICLE NUMBER(S)
006-14000



## Mounting accessories

### CEILING CLIP

COLOUR	ARTICLE NUMBER(S)
transparent	034-11636



## Mounting accessories

### CABLE SUSPENSION

ARTICLE NUMBER(S)
005-2122110



### CABLE RAIL

Ø (MM)	ARTICLE NUMBER(S)
1200	005-2491110



[007-93M3037 006-16092Z 046-400301X] The technical data represent rated values for an ambient temperature of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)

or the luminous 27.05.2024

# MINO 60 high lumen

ceiling / suspended system

007-93M3037 006-16092Z 046-400301X



Project / Type

Notes

Count / Date

## Electrical accessories

### THROUGH WIRE

TYPE	ARTICLE NUMBER(S)
3 x 1,5 mm <sup>2</sup>   10 pieces	004-90003
5 x 1,5 mm <sup>2</sup>   10 pieces	004-90005



## Electrical accessories

### CANOPY / FEEDER CABLE

TYPE	COLOUR	ARTICLE NUMBER(S)
3 x 1,5 mm <sup>2</sup>	traffic white	005-2212317
3 x 1,5 mm <sup>2</sup>	jet black	005-2212318
5 x 1,5 mm <sup>2</sup>	pure white	005-2212417
5 x 1,5 mm <sup>2</sup>	jet black	005-2212418

