

FRAME 60 high lumen

trim system

007-93M2617 006-16062H 035-0063G



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

grey , RAL9006 ¹

2750 lm/m

IP20

1570 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.65

Optical

High Performance Opal

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

13.2 W

PC1 220-240V

119 lm/W

23 W/m

Physical

trim

length 572 mm

width 77 mm

height 78 mm

1.65 kg

Cutout

length 588 mm


width 66 mm

min. ceiling thickness 8 mm


max. ceiling thickness 25 mm

recessed depth 108 mm

Light distribution



Product drawing



FRAME 60 high lumen

trim system

007-93M2617 006-16062H 035-0063G



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 9 |
| B13 | 13 |
| B16 | 15 |
| B20 | 18 |
| C10 | 18 |
| C13 | 26 |
| C16 | 30 |
| C20 | 36 |

Mounting accessories

END CAPS

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|--------|-----------------|-------------------|
| 1 pair | traffic white | 035-13137 |
| 1 pair | white aluminium | 035-1313G |



Mounting accessories

LINEAR CONNECTOR

| TYPE | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece | 005-40046 |
| 10 pieces | 005-40046.10 |



OPAL COVER LINEAR CONNECTOR

| ARTICLE NUMBER(S) |
|-------------------|
| 006-14000 |



Mounting accessories

MOUNTING BRACKET

| TYPE | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece | 035-10200 |
| 25 pieces | 035-10200.25 |

Electrical accessories

THROUGH WIRE

| TYPE | ARTICLE NUMBER(S) |
|-------------------------------------|-------------------|
| 3 x 1,5 mm ² 10 pieces | 004-90003 |
| 5 x 1,5 mm ² 10 pieces | 004-90005 |

