

MINO 60 high lumen

ceiling / suspended system

007-93M2137 006-16062H 046-4002017



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|-------------------------------|
| Ceiling , Suspended |
| white , RAL 9010 ¹ |
| IP20 |
| 1290 lm |
| 2250 lm/m |

LED

| |
|---|
| 4000 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 99 , R _r : 92 , R _{t(1-15)} : 90 |
| MR 0.81 |
| MDER 0.74 |

Optical

| |
|--------------------------|
| High Performance Opal |
| opal (lambertsch) |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |


Electrical

| |
|------------------------------|
| DALI-2 |
| 220-240 V |
| system 12.1 W |
| system 107 lm/W ³ |
| PC1 |
| 1 DALI Addr. |
| 21 W/m |

Physical

| |
|---------------|
| trim |
| length 572 mm |
| width 60 mm |
| height 80 mm |
| 1.55 kg |

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Installation instructions



Lighting calculator

