

MINO 60 high lumen

ceiling / suspended system

007-93M2037 006-16062H 046-400201X



Project / Type

Notes

Count / Date



General

Ceiling , Suspended
special colours
2080 lm/m
IP20
1190 lm

LED

3000 K
CRI \geq 90
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam \leq 3 SDCM
R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89
MR 0.61
MDER 0.55

Optical

High Performance Opal
PstLM \leq 1.0 ¹
SVM \leq 0.4 ¹

Electrical


DALI-2
13.2 W
PC1 220-240V
90 lm/W
1 DALI Addr.
23 W/m

Physical

trim
length 572 mm
width 60 mm
height 80 mm
1.65 kg

¹ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[007-93M2037 006-16062H 046-400201X] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

27.05.2024