

MINO 60 mid lumen

ceiling / suspended system

007-93L2017 006-16062H 046-400201G



Project / Type	
Notes	
Count / Date	



Luminaire housing made of extruded aluminium profile; angular design; for continuous lighting systems; light tight final end caps made of aluminium (available as an accessory); no visible screws; surface grey powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; luminaire profile for mounting available in advance; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Product drawing



General

Ceiling , Suspended	
grey , RAL9006 ¹	
1240 lm/m	
IP20	
709 lm	

LED

3000 K	
CRI ≥ 90	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam ≤ 3 SDCM	
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89	
MR 0.61	
MDER 0.55	

Optical

High Performance Opal	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Electrical

non DIM	
7.5 W	
PC1 220-240V	
95 lm/W	
13 W/m	

Physical

trim	
length 572 mm	
width 60 mm	
height 80 mm	
1.65 kg	

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

