

FRAME 60 high lumen

trim system

007-9334D37 006-16122Z 035-0123G



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed	
grey , RAL9006 ¹	
2230 lm/m	
IP20	
2610 lm	

LED

tunable white	
2700 K - 6500 K	
CRI ≥ 80	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam ≤ 3 SDCM	
MR 0.48	
MDER 0.44	

Optical

Microprismatic	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Electrical

DALI-2 DT8	
25.3 W	
PC1 220-240V	
103 lm/W	
1 DALI Addr.	
22 W/m	

Physical


length 1172 mm	
width 77 mm	
height 78 mm	
3.2 kg	

Cutout

length 1188 mm	
width 66 mm	
min. ceiling thickness 8 mm	
max. ceiling thickness 25 mm	
recessed depth 108 mm	

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



FRAME 60 high lumen

trim system

007-9334D37 006-16122Z 035-0123G



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	13
B13	16
B16	22
B20	27
C10	21
C13	28
C16	36
C20	45

Mounting accessories

END CAPS

TYPE	COLOUR	ARTICLE NUMBER(S)
1 pair	traffic white	035-13137
1 pair	white aluminium	035-1313G



Mounting accessories

LINEAR CONNECTOR

TYPE	ARTICLE NUMBER(S)
1 piece	005-40046
10 pieces	005-40046.10



OPAL COVER LINEAR CONNECTOR

ARTICLE NUMBER(S)
006-14000



Mounting accessories

MOUNTING BRACKET

TYPE	ARTICLE NUMBER(S)
1 piece	035-10200
25 pieces	035-10200.25

Electrical accessories

THROUGH WIRE

TYPE	ARTICLE NUMBER(S)
3 x 1,5 mm ² 10 pieces	004-90003
5 x 1,5 mm ² 10 pieces	004-90005

