

# FRAME 60 high lumen

trim system

007-9334D37 006-16122Z 035-0123G



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Recessed	
grey , RAL9006 <sup>1</sup>	
2230 lm/m	
IP20	
2610 lm	

## LED

tunable white	
2700 K - 6500 K	
CRI ≥ 80	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam ≤ 3 SDCM	
MR 0.48	
MDER 0.44	

## Optical

Microprismatic	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	

## Electrical

DALI-2 DT8	
25.3 W	
PC1 220-240V	
103 lm/W	
1 DALI Addr.	
22 W/m	

## Physical


length 1172 mm	
width 77 mm	
height 78 mm	
3.2 kg	

## Cutout

length 1188 mm	
width 66 mm	
min. ceiling thickness 8 mm	
max. ceiling thickness 25 mm	
recessed depth 108 mm	

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

