

NOBA 60 suspended 2 lamps

MOVE IT PRO
086-71100358W



Project / Type _____


Notes _____

Count / Date _____



Decorative pendant light inset made of aluminium; 2 lamps; surface anodised gun metal; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2; 220-240 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



wide flood 67° combined

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 1910 | 1.31 |
| 2 | 480 | 2.63 |
| 3 | 210 | 3.94 |
| 4 | 120 | 5.26 |
| 5 | 80 | 6.57 |

Product drawing



General

Ceiling | Track Suspended _____

gun metal _____

Converter Jet Black _____

IP20 _____

2010 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 | R_f: 91 | R_{f(1-15)}: 89 _____

MR 0.59 | MDER 0.53 _____

Optical

wide flood | beam angle 67° _____

PstLM $\leq 1.0^{1,2}$ | SVM $\leq 0.4^{1,2}$ _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC2 | 220-240 V _____

system 19.2 W _____

system 105 lm/W ³ _____

Physical

length 60 mm | width 60 mm | height 60 mm _____

0.92 kg _____

adapter 402 mm _____

suspension 2000 mm _____

¹ combined ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

