

# NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71000397W



Project / Type

Notes

Count / Date



## General

Ceiling , Track Suspended

rose gold

Converter Traffic White

IP20

1010 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

## Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

## Electrical

DALI-2

220-240 V

system 10.0 W

system 101 lm/W<sup>2</sup>

PC2

1 DALI Addr.

## Physical

length 60 mm

width 60 mm


height 60 mm

adapter 402 mm

suspension 2000 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses  
& operating device efficiency

## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	960	1.31
2	240	2.63
3	107	3.94
4	60	5.26
5	38	6.57

## Product drawing



## Installation instructions



## Lighting calculator

