

NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71001347W



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

chrome

Converter Traffic White

IP20

1060 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R_{t(1-15)}: 89

MR 0.81

MDER 0.74

Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

220-240 V

system 10.0 W

system 106 lm/W²

PC2

1 DALI Addr.

Physical

length 60 mm

width 60 mm

height 60 mm


adapter 402 mm

suspension 2000 mm

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Decorative pendant light inset made of aluminium; 1 lamp; surface polished chrome; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2; 220-240 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	1010	1.31
2	250	2.63
3	110	3.94
4	60	5.26
5	40	6.57

Product drawing



Installation instructions



Lighting calculator

