

NOBA 60 suspended 1 lamp

MOVE IT PRO

086-71002367W



Project / Type	
Notes	
Count / Date	



General

Ceiling , Track Suspended
brushed aluminium
Converter Traffic White
IP20
1000 lm

LED

3500 K
CRI \geq 90
L80 / 50000 h
initial MacAdam \leq 2 SDCM
R _g : 97 , R _f : 90 , R _{t(1-15)} : 89
MR 0.7
MDER 0.63

Optical

wide flood
beam angle 67°
PstLM \leq 1.0 ¹
SVM \leq 0.4 ¹

Electrical

DALI-2
220-240 V
system 10.0 W
system 100 lm/W ²
PC2
1 DALI Addr.


Physical

length 60 mm
width 60 mm
height 60 mm
adapter 402 mm
suspension 2000 mm

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Decorative pendant light inset made of aluminium; 1 lamp; surface lacquered in brushed aluminium; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3500 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2; 220-240 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	951	1.31
2	238	2.63
3	106	3.94
4	59	5.26
5	38	6.57

Product drawing



Installation instructions



Lighting calculator

