

NOBA 60 suspended 1 lamp

MOVE IT PRO
086-71001348W



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

chrome

Converter Jet Black

IP20

1060 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89

MR 0.81

MDER 0.74

Optical

wide flood

beam angle 67°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

220-240 V

system 10.0 W

system 106 lm/W²

PC2

1 DALI Addr.

Physical

length 60 mm

width 60 mm


height 60 mm

adapter 402 mm

suspension 2000 mm

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Light distribution



wide flood 67°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 1010 | 1.31 |
| 2 | 250 | 2.63 |
| 3 | 110 | 3.94 |
| 4 | 60 | 5.26 |
| 5 | 40 | 6.57 |

Product drawing



Installation instructions

Lighting calculator

