

NOBA 60 suspended 3 lamps

MOVE IT PRO
086-71200397W



Project / Type


Notes

Count / Date



Decorative pendant light inset made of aluminium; 3 lamps; surface anodised rose gold; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2 220-240V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	2810	1.31
2	700	2.63
3	310	3.94
4	180	5.26
5	110	6.57

Product drawing



General

Ceiling , Track Suspended

rose gold

Converter Traffic White

IP20

2960 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88

MR 0.59

MDER 0.53

Optical

Wide Flood

beam angle 67°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

28.8 W

PC2 220-240V

103 lm/W

1 DALI Addr.

Physical

length 60 mm

width 60 mm

height 60 mm

402 (adapter) mm

suspension 2000 mm

¹ Value of containing product at full load (undimmed)

Lighting calculator

