

# NOBA 60 suspended 3 lamps

MOVE IT PRO  
086-71202368W



Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Decorative pendant light inset made of aluminium; 3 lamps; surface lacquered in brushed aluminium; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3500 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2 220-240V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


## Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	2800	1.31
2	700	2.63
3	310	3.94
4	180	5.26
5	110	6.57

## Product drawing



## General

Ceiling , Track Suspended  
brushed aluminium  
Converter Jet Black  
IP20  
2950 lm

## LED

3500 K  
CRI  $\geq 90$   
L80 / 50000 h  
initial MacAdam  $\leq 2$  SDCM  
R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>t(1-15)</sub>: 89  
MR 0.7  
MDER 0.63

## Optical

Wide Flood  
beam angle 67°  
PstLM  $\leq 1.0$ <sup>1</sup>  
SVM  $\leq 0.4$ <sup>1</sup>

## Electrical

DALI-2  
28.8 W  
PC2 220-240V  
102 lm/W  
1 DALI Addr.

## Physical

length 60 mm  
width 60 mm  
height 60 mm  
402 (adapter) mm  
suspension 2000 mm

<sup>1</sup> Value of containing product at full load (undimmed)

## Lighting calculator

