

NOBA 60 suspended 3 lamps

MOVE IT PRO
086-71200347W



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

chrome _____

Converter Traffic White _____

IP20 _____

2960 lm _____

LED

3000 K _____

CRI \geq 90 _____

L80 / 50000 h _____

initial MacAdam \leq 2 SDCM _____

R_g: 100 , R_f: 91 , R₍₁₋₁₅₎: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

Wide Flood _____

beam angle 67° _____

PstLM \leq 1.0 ¹ _____

SVM \leq 0.4 ¹ _____

Electrical

DALI-2 _____

28.8 W _____

PC2 220-240V _____

103 lm/W _____

1 DALI Addr. _____

Physical

length 60 mm _____


width 60 mm _____

height 60 mm _____

402 (adapter) mm _____

suspension 2000 mm _____


Light distribution



wide flood 67°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 2810 | 1.31 |
| 2 | 700 | 2.63 |
| 3 | 310 | 3.94 |
| 4 | 180 | 5.26 |
| 5 | 110 | 6.57 |

Product drawing



¹ Value of containing product at full load (undimmed)

Lighting calculator

