

# NOBA 60 suspended 3 lamps

MOVE IT PRO  
086-71209348W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Decorative pendant light inset made of aluminium; 3 lamps; surface polished chrome; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2; 220-240 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



**General**

Ceiling | Track Suspended \_\_\_\_\_

chrome \_\_\_\_\_

Converter Jet Black \_\_\_\_\_

IP20 \_\_\_\_\_

2850 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>h-15</sub>: 89 \_\_\_\_\_

MR 0.53 | MDER 0.48 \_\_\_\_\_

**Optical**

wide flood | beam angle 67° \_\_\_\_\_

PstLM  $\leq 1.0^{1,2}$  | SVM  $\leq 0.4^{1,2}$  \_\_\_\_\_

**Electrical**

DALI-2 | 1 DALI Addr. \_\_\_\_\_

PC2 | 220-240 V \_\_\_\_\_

system 28.8 W \_\_\_\_\_

system 99 lm/W <sup>3</sup> \_\_\_\_\_


**Physical**

length 60 mm | width 60 mm | height 60 mm \_\_\_\_\_

adapter 402 mm \_\_\_\_\_

suspension 2000 mm \_\_\_\_\_


## Light distribution



wide flood 67° combined

h (m)	E0° (lx)	ø (m)
1	2710	1.31
2	680	2.63
3	300	3.94
4	170	5.26
5	110	6.57

## Product drawing



<sup>1</sup> combined <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



# NOBA 60 suspended 3 lamps

MOVE IT PRO  
086-71209348W



Project / Type

Notes

Count / Date

### Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

### Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	17
B13	22
B16	28
C10	22
C13	27
C16	35

### Mounting accessories

#### HOOK surface

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

