

# NOBA 60 suspended 3 lamps

MOVE IT PRO  
086-71209358W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Ceiling , Track Suspended \_\_\_\_\_

gun metal \_\_\_\_\_

Converter Jet Black \_\_\_\_\_

IP20 \_\_\_\_\_

2850 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq$  2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

**Optical**

wide flood \_\_\_\_\_

beam angle 67° \_\_\_\_\_

PstLM  $\leq$  1.0<sup>1 2</sup> \_\_\_\_\_

SVM  $\leq$  0.4<sup>1 2</sup> \_\_\_\_\_

**Electrical**

DALI-2 \_\_\_\_\_

220-240 V \_\_\_\_\_

system 28.8 W \_\_\_\_\_

system 99 lm/W<sup>3</sup> \_\_\_\_\_

PC2 \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

**Physical**

length 60 mm \_\_\_\_\_

width 60 mm \_\_\_\_\_


height 60 mm \_\_\_\_\_

adapter 402 mm \_\_\_\_\_

suspension 2000 mm \_\_\_\_\_

<sup>1</sup> combined <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses  
& operating device efficiency


## Light distribution



wide flood 67° combined

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 2710     | 1.31  |
| 2     | 680      | 2.63  |
| 3     | 300      | 3.94  |
| 4     | 170      | 5.26  |
| 5     | 110      | 6.57  |

## Product drawing



## Installation instructions

