

NOBA 60 suspended 3 lamps

MOVE IT PRO
086-71209368W



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; 3 lamps; surface lacquered in brushed aluminium; light inset, incl. high power adapter + converter can be installed flexibly and without tools; power supplied via MOVE IT PRO system track profile; pendant fitting with 2000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC2; 220-240 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling | Track Suspended

brushed aluminium

Converter Jet Black

IP20

2850 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 | R_f: 91 | R_{h-15}: 89

MR 0.53 | MDER 0.48

Optical

wide flood | beam angle 67°

PstLM ≤ 1.0 ^{1 2} | SVM ≤ 0.4 ^{1 2}

Electrical

DALI-2 | 1 DALI Addr.

PC2 | 220-240 V

system 28.8 W

system 99 lm/W³


Physical

length 60 mm | width 60 mm | height 60 mm

adapter 402 mm

suspension 2000 mm


Light distribution



wide flood 67° combined

h (m)	EO° (lx)	ø (m)
1	2710	1.31
2	680	2.63
3	300	3.94
4	170	5.26
5	110	6.57

Product drawing



¹ combined ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

