

# MICRO 10

recessed  
011-8100116F



Project / Type


Notes

Count / Date



Round recessed spotlight in aluminium; surface lacquered in white aluminium; with trim; suitable for ceiling thickness of 10-20 mm; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 95$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;


## Light distribution



flood 39°

h (m)	EO <sup>2</sup> (lx)	ø (m)
1	206	0.71
2	51	1.42
3	23	2.13
4	13	2.84
5	8	3.55

## Product drawing



## General

Showcase | Recessed

white aluminium | RAL 9006 <sup>1</sup>

IP20

Interior

101 lm

fixture 99 lm/W <sup>2</sup>

## LED

4000 K

CRI  $\geq 95$

L85 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 100 | R<sub>f</sub>: 94 | R<sub>f(1-15)</sub>: 96

MR 0.87 | MDER 0.78

## Optical

flood | beam angle 39°

## Electrical

excl. driver

fixture 1.0 W

350 mA

PC3

## Physical

length 20 mm | width 20 mm | height 33 mm

0.02 kg

## Cutout

min. ceiling thickness 10 mm | max. ceiling thickness 20 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses

## Installation instructions



# MICRO 10

recessed  
011-8100116F



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.983	0.957	0.931	0.906	0.881
LSF	1	1	1	1	1

MF

LMF × RSMF × LLMF × LSF

MF

Maintenance Factor

LMF<sup>a</sup>

Luminaire Maintenance Factor

RSMF<sup>a</sup>

Room Surface Maintenance Factor

LLMF

Lamp Lumens Maintenance Factor

LSF

Lamp Survival Factor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Electrical accessories

### POWER SUPPLY EU

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
15 W	145-33-21	011-9211130



## Electrical accessories

### SPLITTER SERIAL

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
3 × socket / 1 × plug	38-30-10	011-9228300
6 × socket / 1 × plug	55-32-10	011-9228600



## Electrical accessories

### EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9221120
1 × socket / 1 × plug	011-9221140
1 × socket / 1 × plug	011-9221180

