

# STADIO 10

semi-recessed  
011-8000116M



Project / Type


Notes

Count / Date



Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in white aluminium; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;

## Light distribution



medium 30°		
h (m)	EO° (lx)	ø (m)
1	198	0.54
2	49	1.07
3	22	1.61
4	12	2.15
5	8	2.68

## Product drawing



## General

Showcase | Surface

tilt max 90°

rotation 360°

white aluminium | RAL 9006

IP20

Interior

65 lm

fixture 105 lm/W <sup>1</sup>

## LED

4000 K

CRI ≥ 95

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 | R<sub>f</sub>: 94 | R<sub>f(1-15)</sub>: 96

MR 0.87 | MDER 0.78

## Optical

medium | beam angle 30°

## Electrical

excl. driver | 1 DALI Addr.

fixture 0.6 W

220 mA

PC3

200 mA

## Physical

length 11 mm | width 11 mm | height 29 mm

0.05 kg

## Cutout

min. ceiling thickness 12.5 mm | max. ceiling thickness 22 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses

## Installation instructions

