

STADIO 10

semi-recessed
011-8000018M



Project / Type


Notes

Count / Date



Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in tar black; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



h (m)	EO° (lx)	ø (m)
1	183	0.54
2	46	1.07
3	20	1.61
4	11	2.15
5	7	2.68

Product drawing



General

Showcase | Surface

tilt max 90°

rotation 360°

tar black | RAL 9021

IP20

Interior

60 lm

fixture 104 lm/W ¹

LED

3000 K

CRI ≥ 95

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 | R_f: 94 | R_{f(1-15)}: 95

MR 0.61 | MDER 0.55

Optical

medium | beam angle 30°

Electrical

excl. driver | 1 DALI Addr.

fixture 0.6 W

220 mA

PC3

200 mA

Physical

length 11 mm | width 11 mm | height 29 mm

0.2 kg

Cutout

min. ceiling thickness 12.5 mm | max. ceiling thickness 22 mm

¹ incl. consideration of optical losses & internal control unit losses

Installation instructions

