

STADIO 10

semi-recessed
011-8000018F



Project / Type _____


Notes _____

Count / Date _____




Cylindrical semi-recessed mounted spotlight miniature spotlight made of aluminium; surface lacquered in black; spotlight head 360° rotatable and 90° tiltable; suitable for ceiling thickness of 12.5-22 mm; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; degree of protection IP20; PC3; plug and play electrical connector system for toolless mounting (available as an accessory); accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



h (m)	EO° (lx)	ø (m)
1	122	0.71
2	31	1.42
3	14	2.13
4	8	2.84
5	5	3.55

Product drawing



General

Showcase | Surface _____

tilt max 90° _____

rotation 360° _____

black | RAL 9021 ¹ _____

IP20 _____

Interior _____

60 lm _____

fixture 105 lm/W ² _____

LED

3000 K _____

CRI ≥ 95 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 102 | R_f: 94 | R_{f(1-5)}: 95 _____

MR 0.61 | MDER 0.55 _____

Optical

flood | beam angle 39° _____

Electrical

excl. driver _____

fixture 0.6 W _____

220 mA _____

PC3 _____

200 mA _____

Physical

length 11 mm | width 11 mm | height 29 mm _____

0.1 kg _____

Cutout

min. ceiling thickness 12.5 mm | max. ceiling thickness 22 mm _____

¹ RAL code
² incl. consideration of optical losses & internal control unit losses

Installation instructions

