

FINA SUPPORT stadio 10

011-2203116S



Project / Type

Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 18° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;



General

Showcase | Standing

rotation 360°

white aluminium | RAL 9006

IP20

Interior

270 lm

optical inset 13 lm/W ¹

LED

4000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 | R_f: 94 | R_{f(1-15)}: 96

MR 0.87 | MDER 0.78

Optical

spot | beam angle 18°

Electrical

excl. driver

PC3 | 24 V


fixture 4.7 W

optical inset 3.5 W

Physical


length 400 mm | width 11 mm | height 29 mm

Light distribution



spot 18°		
h (m)	E0° (lx)	ø (m)
1	329	0.32
2	82	0.64
3	37	0.96
4	21	1.28
5	13	1.59

Product drawing



¹ incl. consideration of optical losses

Installation instructions

