

FINA SUPPORT stadio 10

011-2203018S



Project / Type


Notes

Count / Date




Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 18° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



spot 18°		
h (m)	EO° (lx)	ø (m)
1	300	0.32
2	75	0.64
3	33	0.96
4	19	1.28
5	12	1.59

Product drawing



General

Showcase | Standing

rotation 360°

black | RAL 9021 ¹

IP20

Interior

246 lm

optical inset 12 lm/W ²

LED

3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 | R_f: 94 | R_{f(1-5)}: 95

MR 0.61 | MDER 0.55

Optical

spot | beam angle 18°

Electrical

excl. driver

PC3 | 24 V

fixture 4.4 W

optical inset 3.3 W

Physical

length 400 mm | width 11 mm | height 29 mm

¹ RAL code ² incl. consideration of optical losses

Installation instructions



[‘011-2203018S’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com