

# FINA stadio 10

011-2103118M



Project / Type


Notes

Count / Date




Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; spotlight heads 360° rotatable and 90° tiltable; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

## Light distribution



medium 30°		
h (m)	E0° (lx)	ø (m)
1	183	0.54
2	46	1.07
3	20	1.61
4	11	2.15
5	7	2.68

## Product drawing



### General

Showcase | Recessed

tilt max 90°

rotation 360°

black | RAL 9021<sup>1</sup>

IP20

Interior

360 lm

optical inset 18 lm/W<sup>2</sup>

### LED

4000 K

CRI ≥ 95

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 | R<sub>f</sub>: 94 | R<sub>f(1-15)</sub>: 96

MR 0.87 | MDER 0.78

### Optical

medium | beam angle 30°

### Electrical

excl. driver

PC3 | 24 V

fixture 5.0 W

optical inset 3.4 W

24 V

### Physical

length 400 mm | width 11 mm | height 29 mm

0.69 kg

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

## Installation instructions

