



Project / Type


Notes

Count / Date



Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; spotlight heads 360° rotatable and 90° tiltable; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 18° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;


Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	329	0.32
2	82	0.64
3	37	0.96
4	21	1.28
5	13	1.59

Product drawing



General

Showcase | Recessed

tilt max 90°

rotation 360°

white aluminium | RAL 9006 ¹

IP20

Interior

270 lm

optical inset 13 lm/W ²

LED

4000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 | R_f: 94 | R_{f(1-15)}: 96

MR 0.87 | MDER 0.78

Optical

spot | beam angle 18°

Electrical

excl. driver

PC3 | 24 V

fixture 5.2 W

optical inset 3.5 W

24 V

Physical

length 400 mm | width 11 mm | height 29 mm

0.2 kg

¹ RAL code ² incl. consideration of optical losses

Installation instructions

