



Project / Type

Notes

Count / Date



General

Showcase , Recessed

tilt max 90°

rotation 360°

black , RAL 9021 ¹

IP20

Interior

246 lm

optical inset 12 lm/W²

LED

3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_f: 94 , R_{f(-15)}: 95

MR 0.61

MDER 0.55

Optical

spot

beam angle 18°

Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; spotlight heads 360° rotatable and 90° tiltable; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 18° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Electrical

excl. driver

24 V


fixture 4.9 W

optical inset 3.3 W

PC3

24 V


Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	300	0.32
2	75	0.64
3	33	0.96
4	19	1.28
5	12	1.59

Product drawing



Physical

length 400 mm

width 11 mm

height 29 mm

0.07 kg

¹ RAL code ² incl. consideration of optical losses

Installation instructions





Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.954	0.915	0.879	0.844	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

MOUNTING CHANNEL 90

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	230-17-11	011-9100206
black	230-17-11	011-9100208
white aluminium	430-17-11	011-9100306
black	430-17-11	011-9100308
white aluminium	630-17-11	011-9100406
black	630-17-11	011-9100408
white aluminium	830-17-11	011-9100506
black	830-17-11	011-9100508
white aluminium	1030-17-11	011-9100606
black	1030-17-11	011-9100608
white aluminium	1230-17-11	011-9100706
black	1230-17-11	011-9100708



MOUNTING CHANNEL 90 ANTI-GLARE

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	230-17-15	011-9101206
black	230-17-15	011-9101208
white aluminium	430-17-15	011-9101306
black	430-17-15	011-9101308
white aluminium	630-17-15	011-9101406
black	630-17-15	011-9101408
white aluminium	830-17-15	011-9101506
black	830-17-15	011-9101508
white aluminium	1030-17-15	011-9101606
black	1030-17-15	011-9101608
white aluminium	1230-17-15	011-9101706
black	1230-17-15	011-9101708





Project / Type

Notes

Count / Date

Mounting accessories

MOUNTING CHANNEL 60

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	230-40-11	011-9102206
black	230-40-11	011-9102208
white aluminium	430-40-11	011-9102306
black	430-40-11	011-9102308
white aluminium	630-40-11	011-9102406
black	630-40-11	011-9102408
white aluminium	830-40-11	011-9102506
black	830-40-11	011-9102508
white aluminium	1030-40-11	011-9102606
black	1030-40-11	011-9102608
white aluminium	1230-40-11	011-9102706
black	1230-40-11	011-9102708



Mounting accessories

MOUNTING CHANNEL 45

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	230-17-11	011-9103206
black	230-17-11	011-9103208
white aluminium	430-17-11	011-9103306
black	430-17-11	011-9103308
white aluminium	630-17-11	011-9103406
black	630-17-11	011-9103408
white aluminium	830-17-11	011-9103506
black	830-17-11	011-9103508
white aluminium	1030-17-11	011-9103606
black	1030-17-11	011-9103608
white aluminium	1230-17-11	011-9103706
black	1230-17-11	011-9103708



MOUNTING CHANNEL 45 JUT-OUT

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
white aluminium	230-17-18	011-9104206
black	230-17-18	011-9104208
white aluminium	430-17-18	011-9104306
black	430-17-18	011-9104308
white aluminium	630-17-18	011-9104406
black	630-17-18	011-9104408
white aluminium	830-17-18	011-9104506
black	830-17-18	011-9104508
white aluminium	1030-17-18	011-9104606
black	1030-17-18	011-9104608
white aluminium	1230-17-18	011-9104706
black	1230-17-18	011-9104708





Project / Type

Notes

Count / Date

Mounting accessories

MOUNTING CLIP 90

COLOUR	ARTICLE NUMBER(S)
black	011-9100008



MOUNTING CLIP 60

COLOUR	ARTICLE NUMBER(S)
black	011-9102008



MOUNTING CLIP 45

COLOUR	ARTICLE NUMBER(S)
black	011-9103008



Mounting accessories

MOUNTING TOOL

ARTICLE NUMBER(S)
011-9190000



Mounting accessories

BLIND INSET

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
200 mm	white aluminium	9	011-9109206
200 mm	black	9	011-9109208
400 mm	white aluminium	9	011-9109306
400 mm	black	9	011-9109308
600 mm	white aluminium	9	011-9109406
600 mm	black	9	011-9109408
800 mm	white aluminium	9	011-9109506
800 mm	black	9	011-9109508
1000 mm	white aluminium	9	011-9109606
1000 mm	black	9	011-9109608
1200 mm	white aluminium	9	011-9109706
1200 mm	black	9	011-9109708





Project / Type

Notes

Count / Date

Electrical accessories

POWER SUPPLY 24V EU

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
18 W non dim	130-43-30	011-9212110
35 W non dim	195-43-30	011-9212210
60 W non dim	220-43-30	011-9212310
18 W DALI-2	130-43-30	011-9212130
35 W DALI-2	195-43-30	011-9212230
60 W DALI-2	220-43-30	011-9212330



POWER SUPPLY 24V UL

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
20 W non dim	153-41-32	011-9282110
40 W non dim	210-40-30	011-9282210
60 W non dim	250-40-30	011-9282310
60 W 1-10 V	176-45-32	011-9282320
60 W DALI-2	176-45-32	011-9282330



Electrical accessories

FLEX CONNECTOR

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
electrical		011-9225100
electrical 90°	39-39-9	011-9225200



LINEAR CONNECTOR

TYPE	ARTICLE NUMBER(S)
electrical	011-9225300



Electrical accessories

EXTENSION CABLE

TYPE	ARTICLE NUMBER(S)
1 × socket / 1 × plug	011-9222120
1 × socket / 1 × plug	011-9222140
1 × socket / 1 × plug	011-9222180
1 × socket / 1 × plug 90°	011-9222220
1 × socket / 1 × plug 90°	011-9222240
1 × socket / 1 × plug 90°	011-9222280

