

# FINA stadio 10

011-2103018M



Project / Type


Notes

Count / Date




Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; spotlight heads 360° rotatable and 90° tiltable; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 30° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

## Light distribution



medium 30°		
h (m)	E0° (lx)	ø (m)
1	167	0.54
2	42	1.07
3	19	1.61
4	10	2.15
5	7	2.68

## Product drawing



### General

Showcase | Recessed

tilt max 90°

rotation 360°

black | RAL 9021 <sup>1</sup>

IP20

Interior

330 lm

optical inset 18 lm/W <sup>2</sup>

### LED

3000 K

CRI ≥ 95

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 102 | R<sub>f</sub>: 94 | R<sub>t1-15</sub>: 95

MR 0.61 | MDER 0.55

### Optical

medium | beam angle 30°

### Electrical

excl. driver

PC3 | 24 V

fixture 4.7 W

optical inset 3.1 W

24 V

### Physical

length 400 mm | width 11 mm | height 29 mm

0.06 kg

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

## Installation instructions

