

FINA stadio 10

011-2103018F



Project / Type


Notes

Count / Date



Miniature linear light inset made of aluminium; tubular design; surface lacquered in tar black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); equipped with miniature spotlight heads; spotlight heads 360° rotatable and 90° tiltable; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;


Light distribution



flood 39°

h (m)	E0° (lx)	ø (m)
1	112	0.71
2	28	1.42
3	12	2.13
4	7	2.84
5	4	3.55

Product drawing



General

Showcase | Recessed

tilt max 90°

rotation 360°

tar black | RAL 9021 ¹

IP20

Interior

330 lm

optical inset 18 lm/W ²

LED

3000 K

CRI ≥ 95

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 | R_f: 94 | R_{t(15)}: 95

MR 0.61 | MDER 0.55

Optical

flood | beam angle 39°

Electrical

excl. driver

PC3 | 24 V

fixture 4.7 W

optical inset 3.1 W

24 V

Physical

length 400 mm | width 11 mm | height 29 mm

0.08 kg

¹ RAL code ² incl. consideration of optical losses

Installation instructions

