

FINA SUPPORT lead 30°

011-1306016A



Project / Type _____

Notes _____

Count / Date _____



General

Showcase | Standing _____

rotation 360° _____

white aluminium | RAL 9006 ¹ _____

IP20 _____

Interior _____

1170 lm _____

optical inset 84 lm/W ² _____

LED

3000 K _____

CRI ≥ 97 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 | R_r: 96 | R_[1-15]: 97 _____

MR 0.68 | MDER 0.61 _____

Optical

asymmetric _____

Electrical

excl. driver _____

PC3 | 24 V _____

fixture 18.2 W _____

optical inset 13.9 W _____

19 W/m _____

24 V _____

Physical

length 1000 mm | width 9 mm | height 9 mm _____


¹ RAL code ² incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

