

FINA SUPPORT spot line

30°

011-0306018M



Project / Type

Notes

Count / Date



General

Showcase , Standing

rotation 360°

black , RAL 9021 ¹

IP20

Interior

1080 lm

optical inset 80 lm/W²

LED

3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 , R_r: 94 , R₍₁₋₅₎: 95

MR 0.61

MDER 0.55

Optical

medium

beam angle 32°x46°

Electrical

excl. driver

24 V

fixture 20.1 W

optical inset 13.5 W

PC3

24 V

Physical

length 1000 mm

width 9 mm

height 9 mm

0.12 kg


¹ RAL code ² incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 32°x46° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



[‘011-0306018M’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com