

FINA SUPPORT lead 30°


011-1302118A



Project / Type _____

Notes _____

Count / Date _____



General

Showcase | Standing _____

rotation 360° _____

black | RAL 9021¹ _____

IP20 _____

Interior _____

255 lm _____

optical inset 92 lm/W² _____

LED

4000 K _____

CRI ≥ 97 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 | R_f: 96 | R_{f(1-15)}: 98 _____

MR 0.86 | MDER 0.78 _____

Optical

asymmetric _____

Electrical

excl. driver _____

PC3 | 24 V _____

fixture 3.6 W _____

optical inset 2.8 W _____

21 W/m _____

24 V _____

Physical

length 200 mm | width 9 mm | height 9 mm _____


¹ RAL code ² incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

