

FINA SUPPORT spot line

30°

011-0304118A



Project / Type _____

Notes _____

Count / Date _____



General

Showcase , Standing _____
rotation 360° _____
black , RAL 9021 ¹ _____
IP20 _____
Interior _____
634 lm _____
optical inset 78 lm/W² _____

LED

4000 K _____
CRI ≥ 95 _____
L80 / 50000 h _____
initial MacAdam ≤ 3 SDCM _____
R_g: 99 , R_r: 92 , R₍₁₋₁₅₎: 89 _____
MR 0.76 _____
MDER 0.69 _____

Optical

asymmetric _____

Electrical

excl. driver _____
24 V _____
fixture 12.2 W _____
optical inset 8.2 W _____
PC3 _____
22 W/m _____
24 V _____

Physical

length 600 mm _____
width 9 mm _____
height 9 mm _____
0.68 kg _____


¹ RAL code ² incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

