

# FINA SUPPORT spot line

## 30°

011-0303116A



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 95$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Showcase , Standing

rotation 360°

white aluminium , RAL 9006 <sup>1</sup>

IP20

Interior

422 lm

optical inset 78 lm/W<sup>2</sup>

### LED

4000 K

CRI  $\geq 95$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>(1-5)</sub>: 89

MR 0.76

MDER 0.69

### Optical

asymmetric

### Electrical

excl. driver

24 V

fixture 8.1 W

optical inset 5.4 W

PC3

23 W/m

24 V

### Physical

length 400 mm

width 9 mm

height 9 mm

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

### Installation instructions



[‘011-0303116A’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)

# FINA SUPPORT spot line

## 30°

011-0303116A



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF               | 0.954  | 0.915  | 0.879  | 0.844  | 0.81   |
| LSF                | 1      | 1      | 1      | 1      | 1      |

|                  |                              |                   |                                 |
|------------------|------------------------------|-------------------|---------------------------------|
| MF               | LMF × RSMF × LLMF × LSF      | RSMF <sup>a</sup> | Room Surface Maintenance Factor |
| MF               | Maintenance Factor           | LLMF              | Lamp Lumens Maintenance Factor  |
| LMF <sup>a</sup> | Luminaire Maintenance Factor | LSF               | Lamp Survival Factor            |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Mounting accessories

### MOUNTING POLE L

| TYPE                      | COLOUR          | ARTICLE NUMBER(S) |
|---------------------------|-----------------|-------------------|
| mechanical   180          | white aluminium | 011-9121116       |
| mechanical   180          | black           | 011-9121118       |
| feeder / mechanical   180 | white aluminium | 011-9121136       |
| feeder / mechanical   180 | black           | 011-9121138       |
| mechanical   200          | white aluminium | 011-9121216       |
| mechanical   200          | black           | 011-9121218       |
| feeder / mechanical   200 | white aluminium | 011-9121236       |
| feeder / mechanical   200 | black           | 011-9121238       |
| mechanical   300          | white aluminium | 011-9121316       |
| mechanical   300          | black           | 011-9121318       |
| feeder / mechanical   300 | white aluminium | 011-9121336       |
| feeder / mechanical   300 | black           | 011-9121338       |



## Mounting accessories

### MOUNTING POLE T

| TYPE                          | COLOUR          | ARTICLE NUMBER(S) |
|-------------------------------|-----------------|-------------------|
| mechanical / electrical   180 | white aluminium | 011-9122126       |
| mechanical / electrical   180 | black           | 011-9122128       |
| mechanical / electrical   200 | white aluminium | 011-9122226       |
| mechanical / electrical   200 | black           | 011-9122228       |
| mechanical / electrical   300 | white aluminium | 011-9122326       |
| mechanical / electrical   300 | black           | 011-9122328       |



## Mounting accessories

### MOUNTING POLE Y

| TYPE                          | COLOUR          | ARTICLE NUMBER(S) |
|-------------------------------|-----------------|-------------------|
| mechanical / electrical   180 | white aluminium | 011-9123126       |
| mechanical / electrical   180 | black           | 011-9123128       |
| feeder / mechanical   180     | white aluminium | 011-9123136       |
| feeder / mechanical   180     | black           | 011-9123138       |
| mechanical / electrical   200 | white aluminium | 011-9123226       |
| mechanical / electrical   200 | black           | 011-9123228       |
| feeder / mechanical   200     | white aluminium | 011-9123236       |
| feeder / mechanical   200     | black           | 011-9123238       |
| mechanical / electrical   300 | white aluminium | 011-9123326       |
| mechanical / electrical   300 | black           | 011-9123328       |
| feeder / mechanical   300     | white aluminium | 011-9123336       |
| feeder / mechanical   300     | black           | 011-9123338       |



[011-0303116A] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

30.04.2025

# FINA SUPPORT spot line

## 30°

011-0303116A



Project / Type

Notes

Count / Date

### Electrical accessories

#### POWER SUPPLY 24V EU

| TYPE           | L-W-H (MM) | ARTICLE NUMBER(S) |
|----------------|------------|-------------------|
| 18 W   non dim | 130-43-30  | 011-9212110       |
| 35 W   non dim | 195-43-30  | 011-9212210       |
| 60 W   non dim | 220-43-30  | 011-9212310       |
| 18 W   DALI-2  | 130-43-30  | 011-9212130       |
| 35 W   DALI-2  | 195-43-30  | 011-9212230       |
| 60 W   DALI-2  | 220-43-30  | 011-9212330       |



#### POWER SUPPLY 24V UL

| TYPE           | L-W-H (MM) | ARTICLE NUMBER(S) |
|----------------|------------|-------------------|
| 20 W   non dim | 153-41-32  | 011-9282110       |
| 40 W   non dim | 210-40-30  | 011-9282210       |
| 60 W   non dim | 250-40-30  | 011-9282310       |
| 60 W   1-10 V  | 176-45-32  | 011-9282320       |
| 60 W   DALI-2  | 176-45-32  | 011-9282330       |



### Electrical accessories

#### EXTENSION CABLE

| TYPE                  | ARTICLE NUMBER(S) |
|-----------------------|-------------------|
| 1 × socket / 1 × plug | 011-9222120       |
| 1 × socket / 1 × plug | 011-9222140       |
| 1 × socket / 1 × plug | 011-9222180       |

