



Project / Type _____


Notes _____

Count / Date _____



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase , Standing _____

rotation 360° _____

black , RAL 9021 ¹ _____

IP20 _____

Interior _____

933 lm _____

1210 lm/m _____

optical inset 84 lm/W² _____

LED

3000 K _____

CRI ≥ 97 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_f: 96 , R_{t(1-15)}: 97 _____

MR 0.68 _____

MDER 0.61 _____

Optical

asymmetric _____

Electrical

excl. driver _____

24 V _____

fixture 14.6 W _____

optical inset 11.1 W _____

PC3 _____

19 W/m _____

24 V _____

Physical

length 800 mm _____

width 9 mm _____

height 9 mm _____

¹ RAL code ² incl. consideration of optical losses

Installation instructions

