



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 95$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 32°x46° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Standing

rotation 360°

black | RAL 9021 <sup>1</sup>

IP20

Interior

1300 lm

optical inset 80 lm/W <sup>2</sup>

LED

3000 K

CRI  $\geq 95$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 102 | R<sub>i</sub>: 94 | R<sub>(1-5)</sub>: 95

MR 0.61 | MDER 0.55

Optical

medium | beam angle 32°x46°

Electrical

excl. driver

PC3 | 24 V

fixture 24.1 W

optical inset 16.1 W

24 V

Physical

length 1200 mm | width 9 mm | height 9 mm

square

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

Installation instructions

