



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Standing

rotation 360°

black | RAL 9021 ¹

IP20

Interior

1150 lm

optical inset 71 lm/W ²

LED

3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 | R_f: 94 | R_{f(1-5)}: 95

MR 0.61 | MDER 0.55

Optical

asymmetric

Electrical

excl. driver

PC3 | 24 V

fixture 24.1 W

optical inset 16.1 W

21 W/m

24 V

Physical

length 1200 mm | width 9 mm | height 9 mm

square

¹ RAL code ² incl. consideration of optical losses

Installation instructions

