

FINA SUPPORT spot line

011-0206116M



Project / Type _____

Notes _____

Count / Date _____



General

Showcase | Standing _____

rotation 360° _____

white aluminium | RAL 9006 ¹ _____

IP20 _____

Interior _____

1190 lm _____

optical inset 87 lm/W ² _____

LED

4000 K _____

CRI ≥ 95 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 | R_r: 92 | R_{t(1-15)}: 90 _____

MR 0.76 | MDER 0.69 _____

Optical

medium | beam angle 32°x46° _____

Electrical

excl. driver _____

PC3 | 24 V _____

fixture 20.3 W _____

optical inset 13.6 W _____

24 V _____

Physical

length 1000 mm | width 9 mm | height 9 mm _____

square _____


¹ RAL code ² incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 32°x46° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

