

# FINA SUPPORT spot line

011-0206016A



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 95$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

## Light distribution



## Product drawing



### General

Showcase | Standing

rotation 360°

white aluminium | RAL 9006 <sup>1</sup>

IP20

Interior

956 lm

optical inset 71 lm/W <sup>2</sup>

### LED

3000 K

CRI  $\geq 95$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 102 | R<sub>f</sub>: 94 | R<sub>(f-15)</sub>: 95

MR 0.61 | MDER 0.55

### Optical

asymmetric

### Electrical

excl. driver

PC3 | 24 V

fixture 20.1 W

optical inset 13.5 W

21 W/m

24 V

### Physical

length 1000 mm | width 9 mm | height 9 mm

square

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

## Installation instructions

