



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 32°x46° beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Standing

rotation 360°

black | RAL 9021 ¹

IP20

Interior

956 lm

optical inset 88 lm/W ²

LED

4000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 | R_r: 92 | R_{t(1-15)}: 90

MR 0.76 | MDER 0.69

Optical

medium | beam angle 32°x46°

Electrical

excl. driver

PC3 | 24 V

fixture 16.2 W

optical inset 10.9 W

24 V

Physical

length 800 mm | width 9 mm | height 9 mm

square

¹ RAL code ² incl. consideration of optical losses

Installation instructions

