



Project / Type _____

Notes _____

Count / Date _____



General

Showcase | Recessed
 black | RAL 9021¹
 IP20
 Interior
 1200 lm
 1020 lm/m
 optical inset 73 lm/W²

LED

3000 K
 CRI ≥ 97
 L85 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 99 | R_r: 96 | R_{t(1-15)}: 97
 MR 0.68 | MDER 0.61

Optical

Opal | opal (lambertsch)

Electrical

excl. driver
 PC3 | 24 V
 fixture 21.8 W
 optical inset 16.5 W
 19 W/m
 24 V

Physical

length 1200 mm | width 9 mm | height 9 mm
 0.1 kg


¹ RAL code ² incl. consideration of optical losses

Installation instructions



Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

