

FINA SUPPORT spot line


011-0203018A



Project / Type _____

Notes _____

Count / Date _____



General

Showcase | Standing
rotation 360°
black | RAL 9021¹
IP20
Interior
382 lm
optical inset 71 lm/W²

LED

3000 K
CRI ≥ 95
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 102 | R_f: 94 | R_{f(1-15)}: 95
MR 0.61 | MDER 0.55

Optical

asymmetric

Electrical

excl. driver
PC3 | 24 V
fixture 8.0 W
optical inset 5.4 W
23 W/m
24 V

Physical

length 400 mm | width 9 mm | height 9 mm
0.07 kg
square


¹ RAL code ² incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

